
## **SR326F**

# Nylon Sliding Cable Chain with un-screwable split cross pieces with holes

Strong double share Sideband & Frame construction with large anti-friction triple-pin. Un-screwable nylon split cross pieces with different hole combinations. The chain incorporates large sliding-skid surfaces to offer durability even, with high speed/loads. As standard the chain comes with frames every link.



| Pin |               |  |
|-----|---------------|--|
|     | Part.no PG307 |  |


#### **Technical characteristics**

| Speed        | 2 m/s              |
|--------------|--------------------|
| Acceleration | 4 m/s <sup>2</sup> |

For higher requirements please consult our technical dept.

| Α   | В  | N.    | Ø     | R                   | Weight/m | Chain            |
|-----|----|-------|-------|---------------------|----------|------------------|
| mm  | mm | holes | mm    | mm                  | kg       | Part Number      |
| 89  | 59 | 2     | 22    | 107-150-200-250-300 | 1,95     | SR326001 □ □ □ * |
| 155 | 59 | 6     | 17    | 107-150-200-250-300 | 2,20     | SR326002□□□*     |
| 193 | 59 | 6+2   | 17+20 | 107-150-200-250-300 | 2,45     | SR326003 □ □ □ * |
| 214 | 59 | 6     | 25    | 107-150-200-250-300 | 2,70     | SR326004□□□*     |
| 113 | 59 | 3     | 23    | 107-150-200-250-300 | 2,10     | SR326005 □ □ □ * |

\*Complete the code by inserting the value of the radius (R): Ex. SR326001 1 5 0



| R   | Н   | N   | М    |
|-----|-----|-----|------|
| mm  | mm  | mm  | mm   |
| 107 | 272 | 280 | 625  |
| 150 | 358 | 430 | 1000 |
| 200 | 458 | 605 | 1440 |
| 250 | 558 | 775 | 1875 |
| 300 | 658 | 945 | 2315 |

Length of chain (L) Half travel distance  $(\frac{LS}{2})$ plus length of curve (M)

$$L = \frac{LS}{2} + M$$



#### **End Brackets**

The end brackets set allows the two ends of the chain to be attached to the equipment. One set includes two pivoting end brackets to be installed at the moving point and two standard steel end brackets to be installed at the fixed point.

**Bright Zinc Plated Steel Bright Zinc Plated Steel** Type\*\*\* Movable Type\*\*\* (moving point) (fixed point)





Fig. A Chain fixed outside the radius. (Fig A)



| Chain    | F   |
|----------|-----|
| Туре     | mm  |
| SR326001 | 41  |
| SR326002 | 107 |
| SR326003 | 145 |
| SR326004 | 166 |
| SR326005 | 65  |

#### **Bright Zinc Plated Steel Type Part Numbers**

Complete Set Assembled Chain **End Brackets** Set Type SR32600.. A326KM

**Complete Set Unassembled** Chain **End Brackets** Type Set SR32600... A326K


\*\*\* Available on request in stainless steel

### Serie Sliding

**SR326F Nylon Sliding Cable** Chain with un-screwable nylon split cross pieces with holes







Steel laminar cover.

Special tool to remove the connecting pivots: Part Number PZ036.



For further information please consult Brevetti Stendalto's **Technical Office**