
SR328BNylon Sliding Cable Chain with un-screwable aluminium rods

Inner height (D) 48 mm

Strong double share Sideband & Frame construction with large anti-friction triple-pin. The chain incorporates large sliding-skid surfaces to offer durability, even with high speed/loads. The Alu-rod frames are un-screwable from inner and outer radius. As standard the chain comes with frames every second link, on request with frames every link. Separator systems are available.



Separator	
- Unassembled	Part.no S3000F
- Assembled	Part.no S3000FMC
Pin	
	Part.no PG328TP

Technical characteristics


Speed	3,5 m/s
Acceleration	8 m/s ²

For higher requirements please consult our technical dept.

Α	В	С	D	R	Weight/m	Chain
mm	mm	mm	mm	mm	kg	Part Number
162	79	100	48	150-180-200-230-280-400	2,50	SR328B100 □ □ *
212	79	150	48	150-180-200-230-280-400	2,60	SR328B150 □ □ □*
262	79	200	48	150-180-200-230-280-400	2,75	SR328B200 □ □ □ *
312	79	250	48	150-180-200-230-280-400	2,90	SR328B250 □ □ □ *
362	79	300	48	150-180-200-230-280-400	3,00	SR328B300 □ □ □ *
C+62	79		48	150-180-200-230-280-400	SR	328B 🗆 🗆 🗆 🗆 🗆 **

*Complete the code by inserting the value of the radius (R): Ex. SR328B100 1 5 0

**Complete the code by inserting the value of the quote C and the radius (R): Ex. SR328B 1 2 3 1 5 0 Chain equipped with aluminium rods every pitch: complete the code by inserting the letter D. Ex. SR328B100150 D



R	Н	N	M
mm	mm	mm	mm
150	379	425	955
180	439	530	1220
200	479	600	1395
230	539	700	1655
280	639	875	2095
400	879	1285	3145

Length of chain (L) Half travel distance (LS) plus length of curve (M)

$$L = \frac{LS}{2} + M$$



End Brackets

The end brackets set allows the two ends of the chain to be attached to the equipment. One set includes two pivoting end brackets to be installed at the moving point and two standard steel end brackets to be installed at the fixed point.

Bright Zinc Plated Steel
Movable Type***
(moving point)
Bright Zinc Plated Steel
Type***
(fixed point)






Fig. A Chain fixed outside the radius. (Fig A)





Chain	F
Туре	mm
SR328B100	87
SR328B150	137
SR328B200	187
SR328B250	237
SR328B300	287
Special widths F=A-75	

Bright Zinc Plated Steel Type Part Numbers

Complete Set Assembled	
Chain	End Brackets
Туре	Set
SR328B	A328KM

Complete Se	et Unassembled
Chain	End Brackets
Туре	Set
SR328B	A328K

^{***} Available on request in stainless steel


Serie Sliding

SR328B
Nylon Sliding Cable
Chain
with un-screwable
aluminium rods





Supplementary movable separators.



Steel laminar cover.

Special tool to remove the connecting pivots:
Part Number PZ038.



For further information please consult Brevetti Stendalto's Technical Office