

Serie Sliding


SR329CU

Nylon Sliding Cable Chain with opening aluminium covers

Inner height (D) 75,5 mm

Strong double share Sideband & Frame construction with large anti-friction triple-pin. The chain incorporates large sliding-skid surfaces to offer durability, even with high speed/loads. Aluminium covers are opening from inner radius or outer radius.

Vertical separators are available



Separator

- Unassembled Part.no S309S
- Assembled Part.no S309SMCI for chain opening outer radius
- Assembled Part.no S309SMCE for chain opening inner radius

Pin

Part.no PG329

Technical characteristics

3

Speed	3 m/s
Acceleration	13 m/s ²

For higher requirements please consult our technical dept.

A mm	B mm	C mm	D mm	R mm	Weight/m kg	Chain Part Number
128	107	64	75,5	200-250-300-350-400-500-600	5,34	SR329CU064□□□*
148	107	84	75,5	200-250-300-350-400-500-600	5,70	SR329CU084□□□*
173	107	109	75,5	200-250-300-350-400-500-600	6,11	SR329CU109□□□*
180	107	116	75,5	200-250-300-350-400-500-600	6,24	SR329CU116□□□*
203	107	139	75,5	200-250-300-350-400-500-600	6,62	SR329CU139□□□*
243	107	179	75,5	200-250-300-350-400-500-600	7,33	SR329CU179□□□*
278	107	214	75,5	200-250-300-350-400-500-600	7,96	SR329CU214□□□*
304	107	240	75,5	200-250-300-350-400-500-600	8,40	SR329CU240□□□*
328	107	264	75,5	200-250-300-350-400-500-600	8,80	SR329CU264□□□*
354	107	290	75,5	200-250-300-350-400-500-600	9,26	SR329CU290□□□*
378	107	314	75,5	200-250-300-350-400-500-600	9,68	SR329CU314□□□*
404	107	340	75,5	200-250-300-350-400-500-600	10,12	SR329CU340□□□*
428	107	364	75,5	200-250-300-350-400-500-600	10,55	SR329CU364□□□*
483	107	419	75,5	200-250-300-350-400-500-600	11,73	SR329CU419□□□*
552	107	488	75,5	200-250-300-350-400-500-600	12,91	SR329CU488□□□*

*Complete the code by inserting the value of the radius (R): Ex. SR329CU116 □□□

R mm	H mm	N mm	M mm
200	506	595	1345
250	606	765	1780
300	706	940	2220
350	806	1110	2655
400	906	1280	3095
500	1106	1625	3970
600	1306	1965	4845



Serie Sliding

SR329CU

Nylon Sliding Cable
Chain with opening
aluminium covers

3

End Brackets

The end brackets set allows the two ends of the chain to be attached to the equipment. One set includes two pivoting end brackets to be installed at the moving point and two standard steel end brackets to be installed at the fixed point.

Bright Zinc Plated Steel
Movable Type***
(moving point)

Bright Zinc Plated Steel
Type***
(fixed point)






Fig. A
Chain fixed outside the radius. (Fig A)



Chain Type	F mm
SR329CU064	40
SR329CU084	60
SR329CU109	85
SR329CU116	92
SR329CU139	115
SR329CU179	155
SR329CU214	190
SR329CU240	216
SR329CU264	240
SR329CU290	266
SR329CU314	290
SR329CU340	316
SR329CU364	340
SR329CU419	395
SR329CU488	464

Chain Type	F1 mm
SR329CU064	51
SR329CU084	71
SR329CU109	96
SR329CU116	103
SR329CU139	126
SR329CU179	166
SR329CU214	201
SR329CU240	227
SR329CU264	251
SR329CU290	277
SR329CU314	301
SR329CU340	327
SR329CU364	351
SR329CU419	406
SR329CU488	475


Bright Zinc Plated Steel Type Part Numbers

Complete Set Assembled
Chain End Brackets
Type Set
SR329CU.. A329CU□□□*KM

Complete Set Unassembled
Chain End Brackets
Type Set
SR329CU.. A329CU□□□*K

* Inner width (C)

*** Available on request in stainless steel



How to open the cover

For further information please
consult Brevetti Stendalto's
Technical Office